

Koch-Glitsch Corporate Headquarters

| nits) | email: info.wichita@kochglitsch.com |
|-------|---|
| | tel: 316-828-5110 fax: 316-828-7985 |
| 4111 | E. 37th St. North, Wichita, KS 67220, USA |

.

| Fray I | Design | Tower | Specification | Shee | t (U.S. Units) |
|---------------|--------|-------|----------------------|------|----------------|
| | .f | | | | |

| Contact Information | End User Contact Information |
|--|---|
| Name | End User Company |
| Title | Address |
| Company | City, State, Zip |
| Address | Country |
| City, State, Zip | Inquiry Date |
| Country | Date Quotation Required |
| Email | Date Equipment Required |
| Phone | |
| Your Reference No. | |
| New or Existing Tower? ¹ New Existing | |
| - | Column Name Tower Manhole / Column Access I.D. (in) |
| | |
| č | d to Tower Attachments No Welding Permitted |
| Applicable Tray Type: Movable Fixed Valve | Other (specify) |
| Tray Numbers | |
| Total Tray Quantity in Section | |
| Tower Inside Diameter ⁺ (ft-in) | |
| Trav Spacing [†] (in) | |
| Number of Liquid Passes [†] | |
| | |
| Operating Pressure (psia) | |
| | |
| Internal Conditions: Vapor to Tray | |
| | |
| | |
| Viscosity (cP) | |
| Temperature (°F) | |
| Internal Conditions: Liquid from Tray | |
| Flow Rate (lb/hr) [§] | |
| Density (lb/ft³)§ | |
| Surface Tension (dyna/om) | |
| Viscosity (cP) | |
| Foaming Tendency/System Factor | |
| | |
| Operating Range % (V/L) | |
| Mechanical Data: Material | |
| Tray Deck [‡] | |
| Cap or valve [‡] | |
| Hardware [‡] | |
| Deal Thicknesst (revers) | |
| Current Diner Midth 9 Thickness (in) | |
| | |
| Corrosion Allowance | |
| | |
| Tower Attachments (in) | |



| Stream I.D. | Description | Above/ Below Tray | Phase [#] | Liquid Fraction (mass) | Pressure (psia) | Temp. (°F) | Flow Rate (Ib/hr) | Density [#] (lb/ft³) | Viscosity (cP) | Surface Tension (dyne/cm) |
|-------------|-------------|-------------------------|--------------------|------------------------------|--------------------|---------------|-------------------------|----------------------------------|-------------------|---------------------------------|
| | | | | | | | | | | |
| | | | | | | | | | · | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | · | |
| | | | | | | | | | | |
| | | | | | | | | | | |

- ¹ If existing please provide vessel elevation, orientation drawing, and drawings of existing tower attachments (or Koch-Glitsch drawing number if applicable).
- [†] May be specified or left to the judgment of Koch-Glitsch.
- [‡] Material of construction to be specified by client.
- [#] If mixed phase, specify physical properties of both phases.
- [§] Internal vapor and liquid loadings at the limiting sections are required to ensure proper equipment design. Simulation tray-to-tray hydraulic output may be submitted in lieu of this form. Densities and mass flow rate are required at actual tower conditions of temperature and pressure.

Please provide any additional information that will help with your design and describe any documents you will send. Include relevant drawings of existing equipment so that we may design a compatible solution. Use more than one sheet if necessary.

Comments/Sketch