

Variflame & Dynaswirl-LN Burners

Low NOx, High-Efficiency Burners for Watertube Boilers

Proven NOx Reduction for Single-Burner Boilers

The Variflame™ burner delivers high-efficiency performance in gas-fired package boilers with NOx emissions as low as 20 ppm (41 mg/Nm³) at 3 percent O₂. Using advanced air-fuel staging techniques, the Variflame burner can operate with or without flue gas recirculation (FGR).

- + Reduces NOx, CO, VOC and particulate emissions
- + Robust and reliable combustion performance
- + High turndown for maximum operating flexibility
- + Reliable flame with a wide range of excess air operation
- + Simultaneous gas and oil firing capability
- + For gas- or oil-fired boilers with heat inputs from 30 to 400 MMBtu/hr (8.8 to 117 MW) per burner
- + Advanced air-fuel staging and FGR for cost-efficient low NOx performance
- + Advanced oil tip design with low atomizing steam usage
- + Quick ramp rate provides a rapid response to load swings

Clean Combustion Made Simple

With no moving parts during operation, the Variflame burner's design delivers reliable performance in the toughest applications.

- + **Air Register:** Turbulence-free axial airflow, the optimized shape minimizes pressure loss through the burner and maximizes velocity.
- + **Swirler:** Produces stable flames and enables thorough mixing.
- + **Throat:** Precisely matched with the register and swirler design to provide an aerodynamically stabilized flame.
- + **Gas Burner:** Unique injector orientation provides fuel staging within the flame envelope, reducing thermal NOx formation.
- + **Oil Burner:** Advanced oil gun tip designs achieve precisely controlled flame geometry.



*Coen and Hamworthy Combustion, available only through JZHC, are the most installed brands for industrial steam generation. **That's smart. That's JZHC.***

- + *Advanced design*
- + *Rugged construction*
- + *Reliable operation*
- + *Single or multi-burner applications*

Dynaswirl-LN™ Low-NOx Gas/Oil Burner for Multi-Burner Boilers

Improve your overall boiler performance while lowering NOx emissions with the high-efficiency, gas/oil-fired burner that's built to last. Designed for heat inputs ranging from 30 to 300 MMBtu/hr (8.8 to 88 MW) per burner, the Dynaswirl-LN burner is capable of simultaneous gas and oil firing. CFD modeling guarantees equal distribution of combustion air and FGR for remarkably efficient operation.

- + Up to 50% NOx reduction over conventional burners; and up to 90% reduction when combined with FGR, over-fire air (OFA) or burners out of service (BOOS)
- + Operable with stack O₂ levels of 0.5% or less
- + Extremely stable combustion minimizes boiler vibration
- + Reliable flames with FGR rates as high as 45%
- + High turndown of 8:1 on oil and up to 20:1 on gas
- + Low CO, particulate and opacity emissions
- + Reduced downtime, maintenance, fuel and operating costs

Pneumatic Air Slide – Providing Reliable On/Off Control

The pneumatic air slide allows for simplified “on/off” air-flow control, eliminating the need for complex modulating devices. The heavy-duty slide closes the air inlet to burners out of service, allowing control of furnace excess oxygen levels through the remaining burners. When closed, cooling air flows through the register to prevent front-end components from overheating. The results? Proven reliability, reduced maintenance and lower operating cost.

That's smart. That's JZHC.



Global Headquarters

Tulsa, Oklahoma | United States

johnzinkhamworthy.com | +1 918 234 1800

To locate an office in your region, visit johnzinkhamworthy.com/contacts/office-locator